



Waterborne paint defoamer

RP-6415

Features and advantages:

RP-6415 is a mixture of wax emulsion, mineral oil and non-ionic surfactant. It is widely used in waterproof coating, emulsion polymerization and water-based coating system. It can also be used in the foam suppression of pigment filler and printing glue and wood system, and the effect is long-lasting.

- It has excellent continuous anti-bubble effect and has very good compatibility.
- Strong versatility, suitable for single, two-component waterproof system.
- Strong compatibility, good stability, high efficiency, wide spectrum.

Product Specifications:

appearance	Translucent colorless - light yellow viscous liquid
Active ingredient	100%
Specific gravity	0.89 g/ml
Ionic type	nonionic
Water solubility	Disperse in water, easily emulsified



Applications: waterproof coatings, various emulsions, water-based binders, various inorganic slurries.

Usage and dosage:

It can be added to the paint in the form of the original, the recommended dosage is 0.1%-0.3%. Add 50% of the mass in the grinding stage and the remaining 50% in the paint mixing stage (before adding the emulsion) until the best results are achieved. Stir well or shake well before use. (The stratification in the storage process does not affect the use efficiency) below 5 ° C will be solidified or stratified, before use below 5 ° C, please use a warm bath to 30-40 ° C and fully mixed, will not affect the use effect

Packing: 16 kg iron drum, 25 kg, 180 kg plastic drum packing.

Storage and precautions: no frost, below 40°C, 12 months