



---

---

## Rheological agent

### RT-3415

#### Features and advantages:

RT-3415 is a specially modified polyamide, which can be used with hydrophilic silica or bentonite to significantly improve the flow resistance of coatings and adhesives. Especially suitable for two-component epoxy systems, including solvent-based, solvent-free types. The amount of addition depends on the amount of hydrophilic silica in the formula.

#### Product specifications:

appearance	Yellow viscous liquid
Non-volatile portion of	99±1%
The proportion of	0.99g/cm <sup>3</sup>
Viscosity/mPa, s	10000-20000

#### Application scope:

- (1) Anti-flow hanging in epoxy sealant system.
- (2) flow resistance in adhesives and coatings.

**Recommended dosage:** for use in epoxy sealant, the recommended dosage is 1-2% of the total curing agent formula

**Usage:** add the additive to the system, stir and disperse evenly.

Tianjin Ruike Chemical Co. LTD

Tel:+86 18526852692

Add:Room 116-11, 160 Xiangyuan Road, Jingjin Science and Technology Valley Industrial Park, Wuqing District, Tianjin

[tjrkhg@126.com](mailto:tjrkhg@126.com)

[www.rk-chem.com](http://www.rk-chem.com)



---

**Packing:** net weight 25Kg/ drum, 200kg/ drum.

**Storage:**

- 1, away from high temperature and fire;
- 2, placed in a cool and ventilated place;
- 3, please seal after use;
4. Shelf life is 12 months.