

Dispersant

RD-9775

Features and Advantages:

RD-9775 is a kind of polymer dispersing agent, widely used in high solid solvent containing coatings and UV curing system, for carbon black, organic pigments and inorganic pigments have shown very excellent grinding dispersion effect, good versatility, good viscosity reduction effect, can also be used in the production of oil color paste.

Product Specifications:

appearance	Yellow-brown liquid/solid	
Significant group	99±1%	
The proportion of	1.03g/cm ³	
Color (Gardner)	≤12	

Recommended dosage calculation formula:

Amount of dispersant (g) = [specific surface area of pigment $(m2/g) \div 500$] × weight of pigment (g)

			Low surface	High
Types of paint	Inorganic	Organic	carbon	surface
	pigments	pigments		carbon
				black



Dispersant				
dosage (100%	0 5 30	7 1 5 0	10 000	40.000
active	0.5-3%	7-15%	10-20%	40-80%
content)				

Method of use:

RD-9775 was dissolved in the mixture of grinding base material, and then pigment was added for grinding.

Scope of application:

- 1. Dispersing and grinding carbon black and organic and inorganic pigments in automotive paint, industrial paint, plastic paint and other systems;
- 2. Dispersive grinding of carbon black, organic pigments and inorganic pigments in UV curing system.

Storage conditions and shelf life:

- 1. Keep away from high temperature and fire sources;
- 2, placed in a ventilated and cool place;
- 3, please seal after use;
- 4. Shelf life: 36 months.

Packing Specifications:

Net weight 25Kg/ barrel, 200kg/ barrel.